



WD Caviar® Blue™

Desktop Hard Drives

WD Caviar Blue hard drives are available with either SATA or PATA interface in a variety of cache sizes with a multitude of available features to deliver rock solid performance and ultra-cool and quiet operation perfect for family and business computing.



INTERFACES

SATA 3 Gb/s
PATA 100 MB/s

MODEL NUMBERS

<i>SATA 3 Gb/s</i>	
WD10EALS	WD2500AAKS
WD6400AAKS	WD2500AAJS
WD5000AAKS	WD1600AAJS
WD3200AAKS	WD800AAJS
WD3200AAJS	

WIDTH/HEIGHT

3.5-inch/1-inch

<i>PATA 100 MB/s</i>	
WD5000AAKB	
WD3200AAJB	
WD2500AAJB	
WD1600AAJB	
WD800AAJB	

ROTATIONAL SPEED

7200 RPM

CAPACITIES

80 GB to 1 TB

Note: Not all products may be available in all regions of the world.

Product Features

Solid performance

With SATA and PATA interfaces, and cache sizes up to 32 MB, this series of drives offer a full range of performance features.

Ultra cool and quiet

Keeping the drive cool enhances reliability. WD continues to develop new and innovative ways to keep drives cool while they are operating which helps protect the drive and the data stored on it.

Capacity

We offer WD Caviar Blue drives with capacities from 80 GB to 1 TB because you can never have too much storage space.

NoTouch™ ramp load technology

The recording head never touches the disk media ensuring significantly less wear to the recording head and media as well as better drive protection in transit.

IntelliSeek™

Calculates optimum seek speeds to lower power consumption, noise and vibration.

ShockGuard™

Instantaneously protects the hard drive against damage from bumps and vibrations while it is running. This technology enables WD Caviar drives to achieve industry-leading shock specifications.

PUT YOUR LIFE ON IT®



WD Caviar Blue

Specifications ¹	1 TB	640 GB	500 GB	500 GB	320 GB	320 GB
Model number	WD10EALS	WD6400AAKS	WD5000AAKS	WD5000AAKB	WD3200AAKS WD3200AAJS	WD3200AAJB
Interface	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	PATA 100 MB/s	SATA 3 Gb/s	PATA 100 MB/s
Formatted capacity	1,000,204 MB	640,135 MB	500,107 MB	500,107 MB	320,072 MB	320,072 MB
User sectors per drive	1,953,525,169	1,250,263,728	976,773,168	976,773,168	625,142,448	625,142,448
LBA support	Yes	Yes	Yes	Yes	Yes	Yes
SATA latching connector	Yes	Yes	Yes	No	Yes	No
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
RoHS compliant ²	Yes	Yes	Yes	Yes	Yes	Yes
Performance						
Data transfer rate (max)						
Buffer to host	3 Gb/s	3 Gb/s	3 Gb/s	100 MB/s ³	3 Gb/s	100 MB/s ³
Host to/from drive (sustained)	126 MB/s	126 MB/s	126 MB/s	126 MB/s	126 MB/s	126 MB/s
Cache (MB)	32	16	16	16	16 (WD3200AAKS) 8 (WD3200AAJS)	8
Rotational speed (RPM)	7200	7200	7200	7200	7200	7200
Reliability/Data Integrity						
Load/unload cycles ⁴	300,000	300,000	300,000	300,000	300,000	300,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁴	<1 in 10 ¹⁴	<1 in 10 ¹⁵	<1 in 10 ¹⁴	<1 in 10 ¹⁵	<1 in 10 ¹⁵
Limited warranty (years) ⁵	3	3	3	3	3	3
Power Management						
12VDC peak (A, ±10%)	1.95	1.375	1.77	1.375	1.77	1.77
Average power requirements (W)						
Read/Write	6.8	8.3	6.0	8.3	5.36	5.36
Idle	6.1	7.7	5.6	7.7	4.92	4.92
Standby	0.7	1.0	0.9	1.0	0.73	0.73
Sleep	0.7	1.0	0.9	1.0	0.73	0.73
Environmental Specifications⁶						
Temperature (°C)						
Operating	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60
Non-operating	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 65	-40 to 65
Shock (Gs)						
Operating (2 ms, read/write)	30	30	30	30	30	30
Operating (2 ms, read)	65	65	65	65	65	65
Non-operating (1 ms)	300	300	350	300	350	350
Average acoustics (dBA) ⁷						
Idle mode	28	25	29	25	29	29
Performance seek mode	33	29	30	29	30	30
Physical Dimensions						
Height (in./mm, max)	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	1.52/0.69	1.32/0.60	0.99/0.45	1.32/0.60	0.95/0.43	0.95/0.43

¹ As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

² WD hard drive products manufactured and sold worldwide after June 1, 2006, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the European Union for electrical and electronic products. The RoHS Directive 2002/95/EC of the European Parliament, which is effective in the EU beginning July 1, 2006, aims to protect human health and the environment by restricting the use of certain hazardous substances in new equipment, and consists of restrictions on lead, mercury, cadmium, and other substances.

³ Maximum burst rate running the Mode 5 Ultra ATA transfer mode.

⁴ Controlled unload at ambient condition.

⁵ The term of the limited warranty may vary by region. Visit support.wdc.com/warranty for details.

⁶ No non-recoverable errors during operating tests or after non-operating tests.

⁷ Sound power level.



WD Caviar Blue

Specifications ¹	250 GB	250 GB	160 GB	160 GB	80 GB	80 GB
Model number	WD2500AAKS WD2500AAJS	WD2500AAJB	WD1600AAJS	WD1600AAJB	WD800AAJS	WD800AAJB
Interface	SATA 3 Gb/s	PATA 100 MB/s	SATA 3 Gb/s	PATA 100 MB/s	SATA 3 Gb/s	PATA 100 MB/s
Formatted capacity	250,059 MB	250,059 MB	160,041 MB	160,041 MB	80,026 MB	80,026 MB
User sectors per drive	488,397,168	488,397,168	312,581,808	312,581,808	156,301,488	156,301,488
LBA support	Yes	Yes	Yes	Yes	Yes	Yes
SATA latching connector	Yes	No	Yes	No	Yes	No
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
RoHS compliant ²	Yes	Yes	Yes	Yes	Yes	Yes
Performance						
Data transfer rate (max)						
Buffer to host	3 Gb/s	100 MB/s ³	3 Gb/s	100 MB/s ³	3 Gb/s	100 MB/s ³
Host to/from drive (sustained)	126 MB/s	126 MB/s	126 MB/s	126 MB/s	126 MB/s	126 MB/s
Cache (MB)	16 (WD2500AAKS) 8 (WD2500AAJS)	8	8	8	8	8
Rotational speed (RPM)	7200	7200	7200	7200	7200	7200
Reliability/Data Integrity						
Load/unload cycles ⁴	300,000	300,000	300,000	300,000	300,000	300,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵
Limited warranty (years) ⁵	3	3	3	3	3	3
Power Management						
12VDC peak (A, ±10%)	1.77	1.77	1.77	1.77	1.77	1.77
Average power requirements (W)						
Read/Write	5.36	5.36	5.36	5.36	5.36	5.36
Idle	4.92	4.92	4.92	4.92	4.92	4.92
Standby	0.73	0.73	0.73	0.73	0.73	0.73
Sleep	0.73	0.73	0.73	0.73	0.73	0.73
Environmental Specifications⁶						
Temperature (°C)						
Operating	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60	0 to 60
Non-operating	-40 to 65	-40 to 65	-40 to 65	-40 to 65	-40 to 65	-40 to 65
Shock (Gs)						
Operating (2 ms, read/write)	30	30	30	30	30	30
Operating (2 ms, read)	65	65	65	65	65	65
Non-operating (1 ms)	350	350	350	350	350	350
Average acoustics (dBA) ⁷						
Idle mode	29	29	29	29	29	29
Performance seek mode	30	30	30	30	30	30
Physical Dimensions						
Height (in./mm, max)	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4	1.028/25.4
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ±.01 in.)	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	0.95/0.43	0.95/0.43	0.95/0.43	0.95/0.43	0.95/0.43	0.95/0.43

¹ As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

² WD hard drive products manufactured and sold worldwide after June 1, 2006, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the European Union for electrical and electronic products. The RoHS Directive 2002/95/EC of the European Parliament, which is effective in the EU beginning July 1, 2006, aims to protect human health and the environment by restricting the use of certain hazardous substances in new equipment, and consists of restrictions on lead, mercury, cadmium, and other substances.

³ Maximum burst rate running the Mode 5 Ultra ATA transfer mode.

⁴ Controlled unload at ambient condition.

⁵ The term of the limited warranty may vary by region. Visit support.wdc.com/warranty for details.

⁶ No non-recoverable errors during operating tests or after non-operating tests.

⁷ Sound power level.



Western Digital, WD, the WD logo, and WD Caviar are registered trademarks in the U.S. and other countries; and WD Caviar Blue, WD Caviar Green, WD Caviar Black, FIT Lab, IntelliSeek, ShockGuard, and NoTouch are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice.

For service and literature:

<http://support.wdc.com>
www.westerndigital.com

800.ASK.4WDC North America
800.832.4778 Spanish
+800.6008.6008 Asia Pacific
00800.27549338 Europe
(toll free where available)
+31.880062100 Europe/Middle East/Africa



© 2010 Western Digital Technologies, Inc. All rights reserved.

Western Digital
20511 Lake Forest Drive
Lake Forest, California 92630
U.S.A.

